


10-24-00

jc813 U.S. PTO

09/694734

10/23/00

10/23/00



Post Mail" mailing label number EL 398 316 800 US.
 of Deposit October 23, 2000

Case No. 10432/28

PATENT APPLICATION TRANSMITTAL LETTER

To the Director of the United States Patent and Trademark Office:

Transmitted herewith for filing is the patent application of: Edward M. House for : DIRECTING PAGES TO A SELECTED OUTPUT DESTINATION OF A PRINTING SYSTEM. Enclosed are:

- ☒ 13 sheet(s) of drawings, 28 pages of application (including title page).
- ☐ Declaration.
- ☐ Power of Attorney.
- ☐ Verified statement to establish small entity status under 37 CFR §§ 1.9 and 1.27.
- ☐ Assignment transmittal letter and Assignment of the invention to : _____.
- ☒ Return-receipt postcard.

Claims as Filed	Col. 1	Col. 2
For	No. Filed	No. Extra
Basic Fee		
Total Claims	26-20	6
Indep. Claims	2-3	0
Multiple Dependent Claims Present		

*If the difference in col. 1 is less than zero, enter "0" in col. 2.

Small Entity	
Rate	Fee
	\$ 355
x\$9=	\$
x\$40=	\$
+\$135=	\$
Total	\$

Other Than Small Entity	
Rate	Fee
	\$ 710
6x\$18=	\$108.00
x\$80=	\$
+\$270=	\$
Total	\$818.00

- ☐ Please charge my Deposit Account No. 23-1925 in the amount of \$: _____. A duplicate copy of this sheet is enclosed.
- ☒ A check in the amount of \$: 818.00 to cover the filing fee and 6 additional claims is enclosed.
- ☒ The Director is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 23-1925. A duplicate copy of this sheet is enclosed.
- ☒ Any additional filing fees required under 37 CFR § 1.16.
- ☒ Any patent application processing fees under 37 CFR §1.17.
- ☐ The Director is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 23-1925. A duplicate copy of this sheet is enclosed.
- ☐ Any filing fees under 37 CFR § 1.16 for presentation of extra claims.
- ☐ Any patent application processing fees under 37 CFR § 1.17.
- ☐ The issue fee set in 37 CFR § 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR § 1.311(b).

10/23/00
 Date

Darin E. Bartholomew
 Darin E. Bartholomew
 BRINKS HOFER GILSON & LIONE
 Registration No. 36,444

"Express Mail" mailing label number EL 398 316 800 US

Date of Deposit. October 23, 2000

Our Case No. 10432/28

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR: EDWARD M. HOUSEL

TITLE: DIRECTING PAGES TO A SELECTED
OUTPUT DESTINATION OF A
PRINTING SYSTEM

ATTORNEY: DARIN E. BARTHOLOMEW
Registration No. 36,444
BRINKS HOFER GILSON & LIONE
P.O. BOX 10395
CHICAGO, ILLINOIS 60610
312 321-4200

DIRECTING PAGES TO A SELECTED OUTPUT DESTINATION OF A PRINTING SYSTEM

FIELD OF THE INVENTION

This invention relates to directing pages to a selected output destination
5 between or among multiple output destinations of a printing system.

BACKGROUND

A digital printing system with multiple media (e.g., paper) supplies and output
destinations may have limited capability in the selection of different output
destinations for the blank or printed output pages. For example, a digital printing
10 system may only allow a user to select one output destination per output set for a print
job. An output set refers to a group of output pages (e.g., printed output pages), which
may be repeated for a single print job. Many digital printing systems generally fail to
allow the operator to choose an output destination for individual pages of the output
set. The user of the printing system may resort to inefficient, labor-intensive, and
15 slow manual sorting processes to handle the proper grouping or collating of papers for
a print job, where individual treatment of one or more output pages in the output set is
required. Thus, a need exists for a printing system that supports selection of different
output destinations, even for the same execution of a single output set of a print job to
reduce printing costs and cycle time.

Some printing systems support special features which allow two output
20 destinations to be used during a single print job. These printing systems typically use
one exit (e.g., a top exit) for printing media of their system as a "purge" tray. For
print jobs executed on such a printing system, the printing system determines if some
of the media loaded in one of the input paper trays is not needed by a current or a
25 successive print job, but must be fed through the system so that the next output set
does not improperly use the wrong media. Accordingly, the printing system
calculates how many unwanted sheets in the input paper tray must be "purged".
However, the printing system may lack the flexibility to let a requestor choose when
to route a page to the "purge" tray to customize a print job. Finally, many printing
30 systems do not support printing on the pages which are sent to the "purge" tray,

further detracting from the ability to tailor a printing job to meet the preferences of a user. Thus, a need exists to enhance a user's control over the routing of pages within a printer to support a customization of a print job.

SUMMARY OF THE INVENTION

5 In accordance with the invention, a printing system comprises at least one input source for storing a medium prior to printing or otherwise operating on the medium. The printing system also includes at least two output destinations for holding or processing the medium after the printing. A user interface supports a user's selection of one of the output destinations for any sheet of a print job in at least one of
10 the input sources prior to the printing. A central processing unit determines a pattern of media feeds for the sheets in each output set to achieve a desired appearance characteristic for the output set or the print job associated with the output destinations. The central data processing unit creates media feed instructions for each sheet based on the pattern of media feeds. The printing system is well suited for outputting a print
15 job in an efficient or customizable manner which may reduce the need for subsequent manual labor or processing of the print job. For example, the routing of pages to different output destinations allows each output destination to be associated with a desired procedure (e.g., a post-printing procedure) that affects a desired appearance of the outputted print job on a page-by-page basis.

20 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of document production system in accordance with the invention.

FIG. 2 is a diagram of a printing system with multiple input sources and output destinations in accordance with the invention.

25 FIG. 3 is a flow chart of a method for directing input pages to one or more selected output destinations of the printing system in accordance with the invention.

FIG. 4 is an example of different input media with a repeating collated sequence in accordance with the invention.

FIG. 5A is an illustrative screen associated with a user interface for making a
30 print job request in accordance with the invention.

FIG. 5B is an illustrative screen demonstrating an early stage of a print job request in accordance with the invention.

FIG. 5C is an illustrative screen showing a print job request in progress following the screen of FIG. 5B.

5 FIG. 5D is an illustrative screen showing a print job request in progress following the screen of FIG. 5C.

FIG. 6A and FIG. 6B are an example of an output set of the printing system in accordance with the invention.

10 FIG. 6C is a chart of a media exit pattern for establishing the output set of FIG. 6A and FIG. 6B.

FIG. 7A and FIG. 7B are an example of output set of the printing system in accordance with the invention.

FIG. 7C is a chart of a media exit pattern for establishing the output set of FIG. 7A and FIG. 7B.

15 FIG. 7D is a chart of an example of an unbalanced media exit pattern for the printing system in accordance with the invention.

FIG. 8 is a flow chart for one embodiment of a method for generating a jam recovery message in accordance with the invention.

20 FIG. 9 is a flow chart for another embodiment for generating a jam recovery message in accordance with the invention.

FIG. 10 is a flow chart for a method for determining a balanced media exit pattern in accordance with the invention.

FIG. 11 is an illustrative screen of the user interface for making a print job request in accordance with the invention.

25 FIG. 12 is an illustrative screen of the user interface showing an example of job requests in accordance with the invention.

FIG. 13 is an illustrative screen of the user interface for making media pattern requests in accordance with the invention.

30 FIG. 14 is an illustrative screen of the user interface showing an example of media pattern requests in accordance with the invention.

DETAILED DESCRIPTION OF THE INVENTION

As used herein, a printing system shall refer to a digital printing system, a duplicating system, or both. This invention relates to a printing system that has at least one input source and at least two output destinations. Further, where multiple input sources are present, each of the input sources may be loaded with different media (e.g., different types or sizes of paper). The printing system 26 may be capable of producing collated output sets of sheets, which are deposited in one or more of the output destinations.

In accordance with the invention, FIG. 1 shows a block diagram of a document production system 19. The document production system 19 includes a remote processing system 20, a communications network 16, a local processing system 24, and a printing system 26. The remote processing system 20 may communicate with the printing system 26 over the communications network 16. The local processing system 24 may communicate directly with the printing system 26.

The document production system 19 facilitates the conversion of a physical representation (e.g., printed page) of an input image to an electronic representation at the local processing system 24 or at the remote processing system 20. The document production system 19 facilitates the transfer of an electronic representation of one or more input images from a remote processing system 20 to the printing system 26 over the communications network 16. The printing system 26 processes the electronic representation in a manner that supports page-by-page routing of output pages to one or more output destinations of the printer 18.

The remote processing system 20 includes a user interface 13 coupled to a computer 11. In turn, the computer 11 is coupled to a scanner 12. In one embodiment, the user interface 13 refers to a graphical user interface that includes a keyboard, a pointing device (e.g., mouse), a display 22, and attendant software instructions to support the keyboard, the pointing device, and the display 22. The computer 11 may represent a source or receptor of one or more print jobs for the printing system 26. For example, the computer 11 may support a print job derived from the operation of the scanner 12. The computer 11 may transmit the print jobs, including electronic representations of input images or documents, to the printing system 26 via the communications network 16. The communications network 16 may

determine how the print jobs are set up. The display 22 of the user interface 13 may have separate screens dedicated to corresponding functions such as displaying the status of the print job and structuring the setup of the print jobs. A screen represents an image that is displayed on the display 22 of the user interface 13.

5 An additional screen allows the operator to view the attributes of the media loaded in the input sources, which are shown in FIG. 2. Another additional screen provides the display of jam recovery instructions so that the user is notified of jam recovery instructions or instantaneous feedback on corrective measures that the user has applied to the printer 18.

10 FIG. 2 is a block diagram of a printing system 26 which has multiple input sources 38 and multiple output destinations 39. Like reference numbers in FIG. 1 and FIG. 2 indicate like elements. Although three input sources 38 and three output destinations 39 are shown, in other embodiments that fall within the scope of the invention, the printing system 26 may have as few as one input source and two output sources. As shown in FIG. 2, the input sources 38 include a first input source 32, a
15 second input source 33, and a third input source 34. The output destinations 39 include a first output destination 35, a second output destination 36, and a third output destination 37.

20 The output destinations 39 may represent several different alternative structures. In accordance with a first alternative, the output destinations 39 may be trays for holding an assortment of different types of media (e.g., paper). In accordance with a second alternative, the output destinations 39 may represent different finishing devices for application to one or more pages after the printing or passage of the pages through the printer 18 without printing on them. Finishing
25 devices may include a stapler, a stacker, a folder, a binder, or another processing station for processing media sent to the output destination. For example, the first output destination 35 may be associated with a stapler that staples groups of paper, the second output destination 36 may be associated with a stacker that stacks paper in sequential order, and the third output destination 37 may be associated with a folder
30 that folds paper to facilitate selective processing of the output pages of an output set of a print job.

FIG. 3 is a flow diagram of a method for directing input pages to one or more selected output destinations of a printer 18 in accordance with the invention. The method of FIG. 3 starts in step S10.

In step S10, the printing system 26 provides at least one input source 38 (e.g., first input source 32) for storing a medium prior to printing or otherwise operating on the medium. The printable medium may represent paper, a polymeric film, a transparency, a photographic quality paper, a cloth sheet, or any other medium suitable for printing.

In step S12, which may occur before, after, or simultaneously with step S10, the printing system 26 provides at least two output destinations 39 for holding or processing the medium after the printing or passage through the printer 18 without printing. In one example, the output destinations 39 comprise paper trays for holding or processing the medium. In another example, the output destinations comprise processing or finishing stations for stapling, binding, folding, or sorting one or more output pages of a print job.

In step S14, the user interface 13 supports the selection of one of the output destinations 39 for any page of a print job in at least one of the input sources 38 prior to the printing. The central processing unit 17 stores a print job identifier and page identifiers (e.g., page numbers) associated with the print job identifier. For each page identifier in the print job, the central processing unit 17 may assign a particular input source 38 to select a desired input medium and an output destination 39. The selection of the output destination 39 may support customized processing of an individual page, such as post-printing processing.

In step S16, the central processing unit 17 determines a pattern of media feeds for the page identifiers or pages of the print job to achieve a desired appearance characteristic or assembled characteristic for a print job associated with the output destinations 39. The central processing unit 17 may organize a print job into a table or database that defines the pattern of media feeds by using one or more of the following fields: job identifier, page identifier, input source, and output destination. Further, the central processing unit 17 may have a printing indicator field in the table or database. The printing indicator expresses whether a printer 18 is supposed to print

on a particular page (with a designated page identifier) or leave the particular page blank prior to or while directing the page to the output destination.

In step S18, the central processing unit 17 determines media feed instructions for routing the pages (e.g., including the printed pages after the printing) of the print job between at least one of the input sources and at least two of the output sources. The central processing unit 17 converts the information in the table or database into printer-readable language or instructions for controlling the printing operation and the direction of pages from the at least one input source 38 to one or more output destination sources 39.

FIG. 4 shows several examples of groups (51, 61, and 71) of sequentially ordered pages for placement in the input source 38 of the printing system 26. A first group 51 of sequentially ordered pages includes tabs 57 that vary in position on each sequential page. Although the first group 51 includes a first page 52, a second page 53, a third page 54, a fourth page 55, and a fifth page 56, an alternate embodiment may use more or less pages for the first group 51. A second group 61 of sequentially ordered pages includes differently colored pages. Although the second group 61 includes a red page 62, a blue page 63, and a green page 64, other colors of pages for the second group 61 fall within the scope of the invention. A third group 71 of sequential ordered pages includes pages with at least two different tab positions 74. The tabs of the third group 71 may have printing on them even when they are first placed in the input source 38. Although the third group 71 includes a first page 72 and a second page 73, the number of pages may be generally commensurate with the number of tab positions in an alternate embodiment. Any of the foregoing input sources 38 may hold letter paper or some other medium instead of the aforementioned media.

A user of the printer 18 may load the first group 51, the second group 61, or the third group 71 into corresponding ones of the input sources 38. For example, the user may load repetitive sets of the first group 51 into the first input source 32, repetitive sets of the second group 61 into the second input source 33, and repetitive sets of the third group 71 into the third input source 34. The user enters a selection of the input sources 38 or a selection of a particular medium or arrangement of media

associated with an input source 38 prior to printing on or otherwise processing the pages in the input sources 38 for a print job.

In general, FIG. 5A through FIG. 5D illustrate various screens that may be displayed on the user interface 13 of the remote processing system 20, the printing system 26, or both. A screen is an image on the display 22 that supports user interaction with the printing system 26. A screen may be displayed on the display 22 to enable a user to control various aspects of the printing system 26.

The screen 101 of FIG. 5A includes a medium indicator 102 (e.g., "Paper"), an exception mode 105, an output destination indicator 106 (e.g., "Exit"), and an editing indicator 107 (e.g., "Edit"). The operational parameters of the medium indicator 102, the exception mode 105, the output destination indicator 106, and the editing indicator 107 may be selected from pull-down menus. A user may reveal a pull-down menu by operation of the pointing device of the user interface 13 or otherwise.

In one example, the user may select a media for the pages to be printed by using the pull-down menu associated with the medium indicator 102. For the media selection indicated by media indicator 102 (e.g., "Paper"), the respective attributes are shown in a text box 104. The user can select a duplex (i.e., two-sided) or simplex (i.e., one-sided) copy using the pull-down menu 105 associated with the exception mode 105.

The user can select an output destination 39 using the pull-down menu associated with the output destination indicator 106. The selected output destination may be referred to generally as a "<JobExit>". If a user designates a particular output destination as a "<JobExit>" for a print job, the particular output destination is regarded as the primary output destination for the print job. The selected output destination determines how a page is directed from an input source 38 to the output destination 39 of the printer 18. The options for pull-down menu of the output destination indicator 106 are: "<JobExit>", "out1", "out2", "out3", "out1+", "out2+", "out3+", where "out1" is an abbreviation for first output destination 35, "out2" is an abbreviation for the second output destination 36, and "out3" is an abbreviation for the third output destination 37.

The jam recovery assistance indicator is represented by the "+" sign, which is appended at a suffix to the foregoing abbreviations of the output destinations. The

jam recovery assistance indicator denotes that the user wants jam recovery assistance for the identified pages and media.

The user types a list of page identifiers (e.g., page numbers) and the keyword “last” on the page identifier list 103 (e.g., "Page List") to apply the previously entered media selection 102, exception mode 105, and output destination 106 to the identified pages set forth on the page identifier list 103. After typing the page numbers into the page identifier list, the user may select an editing option to apply to the print job from an editing menu 107.

FIG. 5B shows a screen as it would look after a user typed a list of page numbers via the user interface 13 on the page identifier list 103. This user also selected a new media called “TabB” by making a selection through a pull-down menu associated with the medium indicator 102. The selected medium is described in the text box 104. Finally, the user selects the option “Insert” from a menu associated with the editing indicator 107.

FIG. 5C shows the appearance of the screen after the procedure of FIG. 5B is executed. The text window 120 of FIG. 5C has four main columns (116, 117, 118, and 119). The leftmost column 116 represents the media indicator 102. The first intermediate column 117 represents a page identifier list 103. The second intermediate column 118 represents the exception mode 105. The rightmost column 119 represents the output destination indicator 106. The instructions in the text window 120 are in an acceptable format for interpretation by the central processing unit 17.

By repeating the entry of data into the user interface 13, the user may eventually populate the text window 120 as shown in FIG. 5D. The screen of FIG. 5D has a plurality of rows, which are labeled from 108 to 115, inclusive. The user types lines 113 and 114 in the text window 120 on the user interface 13 as shown in FIG. 5D. In the leftmost column, the media name is “TabA” of the text window 120 in FIG. 5D. The user wants to print all pages. The user also enables jam recovery messaging using the “+” appended to the desired output destination (e.g., "out2+") as shown in column 119.

In accordance with FIG. 5D, the user could type line 110. Unlike the previous examples, the user does not enable jam recovery messages in line 110. Line 110

allows page nineteen from the job to be sent to the first output destination 35. The user may want part of the print job, such as page nineteen, handled differently by the printing system 26. For example, page nineteen might be a printed instruction sheet for the operator describing what to do with the rest of the printed output. It could also be a status page.

The user could type lines 111, 112 and 115. The instructions of line 111 in the text window 120 would instruct the printing system 26 to print on “color” media for pages seven and fifteen. The instructions of line 112 instruct the printing system 26 to send two unprinted sheets of “color” media would be sent to the first output destination 35 at the end of each set. The instructions of line 115 instruct the printing system to send one unprinted sheet of “color” media to the second output destination 36.

FIG. 6A and FIG. 6B together show an example of an output set 91 which could be generated by the printing system 26. This output set 91 would be generated from thirteen input pages in one or more input sources 38. Here, the print job has already specified the “<JobExit>” to be the second output destination 36 via the user interface 13. The first input source 32 contains paper or another media with two tabs. The second input source 33 contains “letter” media, such as letter size paper. To produce the output set of FIG. 6A and FIG. 6B, the user types lines 108 and 109 of FIG. 5D of the text window 120 into the user interface 13. The media name for the paper with two tabs is “TabB” as shown in column 116 of the text window 120 in FIG. 5D. The user wants to print all pages of the output set with “TabB” for pages 4, 8, and 12. The user also enables jam recovery messaging for page 13 using the “+” appended to the desired output destination as shown in column 119.

FIG. 6A and FIG. 6B shows one output set 91 of a print job consistent with the entry of the input instructions into the text window 120 of the user interface 13. The pages in the group of FIG. 6A are sent to the second output destination 36. The pages of the group of FIG. 6A are actually stacked on top of each other in the second output destination 36. FIG. 6A shows the letter sheets and the “TabB” media sheets next to each other for purposes of clearly identifying the “TabB” media sheets.

First, the central processing unit 17 directs pages one, two, and, three, collectively designated group 92, from the second input source 33 to the second

show them next to each other for purposes of clearly identifying the "TabA" media sheets.

The first pages delivered are pages one, two and three 82, which are collectively designated as group 82. Group 82 are printed on "letter" media. Input page four, designated 83, is printed on the first "TabA" media. Pages five, six and seven, designated group 84, are printed on "letter" media. Before printing page 8, the system sends an unprinted "TabA" media 88 to the first output destination 35 as indicated in FIG. 7B. Input page eight, designated 85, is printed on the third "TabA" media 85. Pages nine, ten and eleven, collectively designated 86, are printed on "letter" media. Page twelve, designated 87, is printed on the fifth "TabA" media. Before printing page twelve 87, the system sends an unprinted "TabA" media 89 to the first output destination 35.

The printing system 26 may build a page feed command for the printer 18 using a special balanced media exit pattern consistent with the table of FIG. 7C. The user enables the special balanced media exit pattern by specifying the term "B" in the page list 103 as shown in line 114 of the text window 120 in column 117 of FIG. 5D. A balanced media exit pattern refers to a media exit pattern that distributes media for a print job in a generally equal or even-handed manner between or among different output destinations 39.

In FIG. 7D, a chart shows a media exit pattern using an unbalanced media exit pattern. For this example, the media repeats for pairs of successive sheets, but the job request in the chart repeats every four sheets. In other respects the media exit pattern of FIG. 7D is similar to the media pattern exit of FIG. 7C.

FIG. 8 shows a flow chart for a method of jam recovery assistance in accordance with the invention. The method of FIG. 8 begins in step S201.

In step S201, if a paper jam is present in the printer 18, the user interface 13 may display messages on the display 22 that instruct the operator to "clear paper" or to remove all paper in the paper path of the printer 18.

In step S202, the printer determines if the jam was cleared by removing the paper. If the jam was cleared, the method continues with step S203. Otherwise, if the jam is not cleared, the method loops back to step S201.

In step S203, the printing system 26 checks if jam recovery is enabled for any page (e.g., page identifier) of a print job. The user may have previously enabled jam recovery by making an entry (e.g., appending a "+" to the output destination) in the user interface 13 on a page-by-page basis for a print job. If jam assistance is enabled for at least one page of the print job the method continues with step S204. Otherwise, if jam assistance is not enabled for any page of the print job, the method ends in step S207.

In step S204, if assistance was enabled, then the system displays a message showing where the printing system 26 is in its media exit pattern 204. The status may be indicated by the page identifier associated with corresponding output destinations. The user interface 13 would inform the user to open the paper supply to verify the top sheet of input media was correct for the current output set. Then, the machine would continue to print the output set. The method of FIG. 8 ends in step S207 following the display of the message in step S204.

FIG. 9 shows an alternative method for jam recovery in accordance with the invention. Like reference characters in FIG. 8 and FIG. 9 indicate like steps or procedures. The method of FIG. 9 is the same as the method of FIG. 8 except the method of FIG. 9 replaces step S204 with step S205. In step S205, which may follow step S203, if assistance was enabled, then the system displays a message telling the user to discard the partially printed set, and to verify that the paper supply is correct to start printing the next set. The method of FIG. 9 ends in step S207 following display of the message in step S205.

FIG. 10 shows a flow chart for the method of balanced media exit pattern determination. A user may invoke or enable the method of FIG. 10 by typing the "B" in column 117 of the text window 120 in FIG. 5D. Before balancing, the media exit pattern might resemble the example of FIG. 7D. After balancing the media exit pattern might resemble the example of FIG. 7C.

Referring to FIG. 10, for each sheet feed handled by the printer 18, one cycle of the method may be invoked. A cycle starts at step S220 with the reception of a sheet feed request via entry from a user interface 13. The cycle may end at any of the point's labeled step S237. FIG. 10 uses various counters (e.g., register values) during a cycle. The values of the counters may be retained for multiple passes through the

method of FIG. 10 until a print job or a set within a print job is complete, where a set may include multiple page feed requests.

In step S221, the printing system 26 determines if the medium currently selected in one of the sources 38 is the correct medium to be processed. If the media currently selected to be fed is the correct medium, which may be referred to as the exit medium, then the method continues with step S222. However, if the media being fed is not the exit media then the method ends in step S237. The end in step S237 means the method is complete and no further action is needed for this sheet feed request. However, a print job or a set in a print job may require the execution of multiple sheet feed requests and multiple executions of the method of FIG. 10.

In step S222, the printing system 26 determines a specific request sum to equal the sum of feed requests entered in the user interface 13 for a particular job exit for the selected medium. For example, the printing system 26 examines the media exit pattern, keeping a count of the number of times the “<JobExit>” is found. Here, a counter may be designated as the specific request sum and the value of the counter is equal to the sum of the media feed requests for the “<JobExit>”. For example, the value of the counter or the specific request sum would be three for the media exit pattern of FIG. 7D because the media exit pattern has three occurrences of “<JobExit>” for each output set.

In step S223 after step S222, the printing system 26 determines if the specific request sum is less than one. The printing system 26 invokes step S223 to check for an invalid media exit pattern. If the media exit pattern is valid, the value of specific request sum is not less than one. Therefore, if the printing system 26 determines that the value of the specific request sum is less than one, the method ends with step S237. Otherwise, if the printing system 26 determines that the value of the specific request sum is not less than one, the method continues with step S224.

In step S224, the printing system 26 determines if the present page being fed is at the start of an output set of a print job. For example, the printing system 26 may reference a page counter that counts each page of an output set for a print job by incrementing the page counter. The set counter is reset at the beginning of each output set. An output set may involve multiple sheet feed requests and cycles of FIG. 10. If the present page is at the start of an output set, the method continues with step

S225. If the present page is not at the start of the an output set, the method continues with step S226.

In step S225, the printing system 26 initializes a number of printing parameters that are used later in the method of FIG. 10. Printing parameters may include a target adjustment value, a specific feed count, and an overall feed count. The target adjustment value may be set from zero to one. For example, the target adjustment value may be set to 0.9 to provide good results or other values consistent with experimental tests. In one embodiment, the specific feed count is set to two and the overall feed count is set to two to prepare for any subsequent processing in accordance with FIG. 10. Further, in step S225, the first sheet of the output set is routed to the job exit. Route to the job exit results in the printing system 26 sending the first media to exit to the "<JobExit>". After step S225, the method may end in step S237 following step S225.

In step S226, the printing system 26 determines if the value of the specific request sum is greater than or equal to two. That is, step S226 determines if there is only one "<JobExit>" request remaining to be executed in the media exit pattern. If the value of specific request sum is not greater than or equal to two, then the method ends in step S237. If the value of the specific request sum is greater than or equal to two, then the method continues with step S227.

In step S227, the printing system 26 determines an overall request sum for the selected medium for the sheet feed request. For example, the printing system 26 examines the media exit pattern, keeping a count of the total number of times any exit (i.e., output destination 39) is requested via the user interface 13. For example, the media exit pattern of FIG. 7C has a total of five occurrences that are split unequally between the first output destination 35 and the second output destination 36. Accordingly, the overall request sum would be five for the example of FIG. 7C. The overall request sum represents the sum of all media feed requests for a media for an output set of a print job.

In step S228, the printing system 26 determines if the value of overall feed count exceeds the value of the overall request sum. The overall feed count represents the total count of the media feeds that have been serviced so far by the printing system 26 for the output set. If the value of the overall feed count is greater than the overall

request sum, the method ends in step S237. The test of step S228 is used to end the method in step S237 if all the required media feeds for the output set of the sheet feed request have been completed. However, if the value of the overall feed count is not greater the overall request sum, the method continues with step S229 because the sheet feed request contains remaining, required media feeds that have not yet been serviced.

In step S229, the printing system 26 determines if the value of overall feed count equals the value of overall request sum. If the value of overall feed count equals the value of overall request sum, the method continues with step S230. If the value of overall feed count does not equal the value of overall request sum, the method continues with step S231.

In step S230, the printing system 26 causes the last requested sheet for the media exit to be routed to the appropriate output destination (e.g., "<JobExit>"). Thus, the printing system 26 may be programmed to allocate the first and last entries in the media exit pattern as "<JobExit>" pages. The "<JobExit>" designation generally affords the assignment of any output destination in a consistent manner within a print job to promote flexibility.

In step S231, the printing system 26 determines values for the first target and the second target to be used in subsequent steps S232 and S233. The first target and the second target may be used to identify pages that are routed to a selected output destination (e.g., a particular job exit) of the printing system 26 for special post-printing processing, for example. The printing system 26 may distinguish between different pages by tracking a specific feed count for a particular output destination and an overall feed count for all output destinations collectively.

The first target may be determined in accordance with the following equation:

$T_1 = F_s * R_o / (R_s - T_A)$, where T_1 is the first target which may represent a highest priority job exit feed target, F_s is a specific feed count which represents a cumulative feed count for a particular job exit, R_o is an overall request sum which represents the sum of feed requests for any or all job exits, R_s is a specific request sum, and T_A is a target adjustment which represents an adjustment of a job exit target (e.g., at least the first target).

The second target may be determined in accordance with the following equation:

$T_2 = F_s * R_o / (R_s + (1 - T_A))$, where T_2 is the second target which represents a lowest priority job exit feed target, F_s is a specific feed count which represents a cumulative feed count for a particular job exit, R_o is an overall request sum which represents the sum of feed requests for any or all job exits, R_s is a specific request sum, and T_A is a target adjustment which represents an adjustment of a job exit target (e.g., the first target and the second target).

In step S232 after step S231, the printing system 26 determines if the overall feed count is greater than or equal to first target. If the overall feed count is greater than or equal to first target, the method continues with step S233. However, if the overall feed count is not greater than or equal to first target, the method continues with step S236.

In step S233, the printing system 26 determines if the overall feed count is less than the second target. If the overall feed count is less than the second target, the method continues with step S234. However, if the overall feed count is not less than second target, the method continues with step S236.

In step S236, the page is routed to a requested output destination 39 (e.g., first output destination). After step S236 in step S235, the overall feed count is incremented by one. After step S235, the method ends in step S237.

In step S234, the specific feed count is incremented (e.g., by one) and page is routed to the particular job exit (e.g., <JobExit>). One of the remaining "<JobExit>" entries may be used for the current media feed in step S234. If the remaining entry is not used for the current media feed, the sheet is routed to the alternate exit specified in the exit pattern media.

In step S235 after step S234, the printing system 26 increments the overall feed count of an exit pattern media feeds. Although the method of FIG. 10 may end in step S237, multiple cycles of FIG. 10 may need to be executed to complete an output set of a print job.

FIG. 11 shows an alternate screen of the user interface 13. The screen of FIG. 11 is similar to the screen of FIG 5D. FIG. 11 replaces the "Exit" with the "Media Exit Pattern" 304. The "Media Exit Pattern" 304 features a "Define Pattern" pull-

down menu. The "Define Pattern" menu may be displayed in an additional column of the display window 305. Like reference numbers in FIG. 5D and FIG. 11 indicate like elements or software features.

The designation of variables or printing control parameters, such as specific feed-request parameter, "<JobExit>", target adjustment, specific feed count, overall feed count, "route to Job Exit", specific request sum and overall request sum, are used for illustrative purposes and actual designations may be different while falling within the scope of the invention.

As shown in FIG. 12, one or more text lines 302 may appear in the text window 305. Like reference numbers in FIG. 11 and FIG. 12 indicate like elements. In the text window 305, one column 303 may show the "+P" which identifies the request as having a media exit pattern associated with it. To remove this pattern, the user can use the "Remove Pattern" from the pull down menu associated with the "Media Exit Pattern" 304. "Edit Pattern" allows changes to a previously established pattern.

In FIG.12, the user has entered a page list on the page identifier list 103. They have selected media called "TabA" in pull-down menu associated with the media indicator 102. The attributes of the media are shown in text box 104. The user has selected "Simplex" in the pull-down menu associated with the exception mode indicator 105. The text box indicates that the user has asked for "TabA" media on three page numbers (e.g., 4, 8 and 12).

In one embodiment, the "Define Pattern" pull-down menu, associated with the media exit pattern 304, has three options: "Define Pattern", "Edit Pattern" and "Remove Pattern". As shown in FIG. 12, the media exit pattern 304 is set in "Define Pattern." "Define Pattern" brings up the screen shown in FIG. 13.

The screen of FIG. 13 supports a user's control of the printing procedure of the printing system 26 via the user interface 13. The screen 351 includes a series of electronic buttons that are arranged in columns (e.g., 359, 360, 361, 362 and 363) and rows (355, 356, 357, and 358). The rows (355, 356, 357, and 358) of the buttons are associated with the following functions: create new insert, use "<JobExit>", use "Exit 1", and use "Exit2". The columns of the buttons are associated with the positions of the pages in an output set of a print job. One column per page of the output set is

preferably displayed in screen 35 or multiple affiliated screens. Here, as shown in FIG. 13, twelve pages per output set are supported, although in other embodiments the number of pages supported may be more or less than shown in FIG. 13. There could be as few as two columns, and there is no upper limit on the number of columns.

5 The first row 355, "Create New Insert" starts out with no check boxes checked as a default selection.

10 In one example, shown in FIG. 14, the user checks the second and fourth check box in the "Create New Insert" row 355. When the printing system 26 prints an output set at print time, the printing system 26 assembles an output set with two unprinted "TabA" sheets added before page two and before page four. The user selects output destinations for the two unprinted "TabA" sheets as follows. First, the user clicks the button in the "Use Exit1" row 357 or another output destination and the second column 360. If the user clicks the "Use Exit1" row for the second column 360, the printing system 26 automatically turns off the button in the Use "<JobExit>" row for the second column 360 because a single indivisible sheet cannot be directed to multiple output destinations. Second, the printing system 26 selects or the user selects the button in the "Use Job Exit" row 356 or another output destination for the fourth column 362. The printing system 26 enforces the selection rule for the buttons that the row must always have the same number of selections as the number of times "TabA" has been requested for the job. Third, the user clicks the button in the "Use Exit1" row 357 for the fourth column 362. This automatically turns off the button in the "Use <JobExit>" row 356 and the fourth column 362. Fourth, the user selects or the printing system 26 selects the button in the "<Use JobExit>" and the fourth column 362.

25 When the user selects the "OK" button 364 in FIG. 14, the selected media exit pattern is saved for the print job with the "TabA" media; the user interface 13 may revert to the screen of FIG. 11. The "Cancel" button 366 in FIG. 14 returns to the screen shown in FIG. 11 without selecting any print media pattern for the "TabA" media. The "Reset" button 365 in FIG. 14 restores the screen to the original state shown in FIG. 13 prior to the user making any entries.

30

The upper limit on the number of "Exit" rows (357 and 358) for display 22 is dependent on the number of exits available on the print engine 38 and supported by the printer 18.

The text box 352 describes the definition of the media. The screen 351 has "Set Exit1 to" and a "Set Exit2 to" which may be defined in accordance with pull-down menus. The pull-down menus associated with "Set Exit1 to" and a "Set Exit2 to" allow the user to define up to two exits (e.g., "Exit1" and "Exit2") in addition to the current "<JobExit>", although other embodiments may allow the definition of more or less exits. The number of exit names which populate these pull down menus are limited to the maximum number supported by the printer 18, rather than any inherent limitation of the software for the screen.

In an alternate embodiment, the "Set Exit1 to" and the "Set Exit2 to" menus may support the selection or assignment of a post-printing process or a post-feeding process for the "Exit1" and "Exit2", respectively. For example, a stapler or stapling station may be assigned to "Exit1" as a post-printing procedure.

The foregoing detailed description is merely illustrative of several physical embodiments of the invention. Physical variations of the invention, not fully described in the specification, may be encompassed within the purview of the claims. Accordingly, any narrower description of the elements in the specification should be used for general guidance, rather than to unduly restrict any broader descriptions of the elements in the following claims

[illegible]

1. A printing system comprising:

at least one input source for storing a medium prior to printing;

at least two output destinations for holding or processing the medium after the printing;

a user interface to support a user's selection of one of the output destinations for any sheet of a print job in the at least one the input source prior to the printing;

a central processing unit configured to determine a pattern of media feeds for each output set of a print job to achieve a desired appearance characteristic of sheets for the output set.

2. The system according to claim 1 wherein the at least one input source comprises an input paper tray.

3. The system according to claim 1 wherein the at least one input source comprises a first dispenser containing a first media with unprinted tabs in different positions on the first media, a second dispenser containing a second media having different colors, and a third dispenser containing a third media with tabs having printing thereon.

4. The system according to claim 1 wherein the pattern comprises a page identifier associated with a printing indicator and a particular output destination.

5. The system according to claim 4 wherein the printing indicator indicates whether or not the printing system is supposed to print on a page of the output set associated with the corresponding page identifier.

6. The system according to claim 1 wherein the output destinations comprise output paper trays.

7. The system according to claim 1 wherein the output destinations are associated with corresponding processing stations for processing pages of the print job on a page-by-page basis.

8. The system according to claim 1 wherein the central processing unit includes a jam handler for providing jam resolution instructions on a display of the user interface.

9. The system according to claim 1 wherein a user request for a print job comprises requesting one particular input source and one particular output destination for affiliation with a page identifier of the print job.

10. The system according to claim 1 wherein the output destinations include a first output destination, a second output destination, and a third output destination; the central processing unit determining a pattern of distribution to the first output destination, the second output destination, and the third output destination to facilitate different post-printing procedures on individual pages of the output set of the print job.

11. The system according to claim 1 wherein the printing system routes a page to a requested output destination or a primary output destination based upon a comparison of a feed count value to at least one target value, wherein the feed count value represents a running count of a number of pages of the output set that have been fed through the printing system from the at least one input source to at least one of the output destinations.

12. The system according to claim 1 wherein the printing system routes a page to a selected output destination, among the output destinations, if feed count value is not less than or equal to a first target or if the feed count value is greater than a second target, where the feed count value refers to a running count of the number of pages that have been fed through the printing system and where the first target and the second target, in effect, establish a range of pages for certain page identifiers.

13. The system according to claim 12 wherein the first target and the second target may be expressed as the following equations, respectively:

$T_1 = F_s * R_o / (R_s - T_A)$, where T_1 is the first target which represents a highest priority job exit feed target, F_s is a specific feed count which represents a cumulative feed count for a particular job exit, R_o is an overall request sum which

represents the sum of feed requests for any or all job exits, R_s is a specific request sum, and T_A is a target adjustment which represents an adjustment of at least the first target.

$T_2 = F_s * R_o / (R_s + (1 - T_A))$, where T_2 is the second target which represents a lowest priority job exit feed target, F_s is a specific feed count which represents a cumulative feed count for a particular job exit, R_o is an overall request sum which represents the sum of feed requests for any or all job exits, R_s is a specific request sum, and T_A is a target adjustment which represents an adjustment of the first target and the second target.

14. The system according to claim 1 wherein a user makes a pattern request by entering the a selection into buttons, associated with the user interface, on a page-by-page basis with a respective choice of output destinations for each page of the output set.

15. A method of printing comprising the steps of:

- storing a medium in at least one input source prior to printing;
- supporting a user's selection of an output destination, among two or more output destinations, for any sheet of a print job in the at least one input source prior to the printing;
- determining a pattern of media feeds for each output set of the print job to achieve a desired appearance characteristic for the output set or a desired assembly of the sheets of the output set.

16. The method according to claim 15 further comprising the step of:

- creating media feed instructions based on the pattern of media feeds.

17. The method according to claim 15 wherein the determining step further comprises associating a page identifier with a printing indicator and a particular output destination to form the pattern of media feeds.

18. The method according to claim 17 wherein the printing indicator indicates whether or not the printing system is supposed to print on a page of the output set associated with the corresponding page identifier.

25. The method according to claim 24 wherein the first target and the second target may be expressed as the following equations, respectively:

$T_1 = F_s * R_o / (R_s - T_A)$, where T_1 is the first target which represents a highest priority job exit feed target, F_s is a specific feed count which represents a cumulative feed count for a particular job exit, R_o is an overall request sum which represents the sum of feed requests for any or all job exits, R_s is a specific request sum, and T_A is a target adjustment which represents an adjustment of at least the first target.

$T_2 = F_s * R_o / (R_s + (1 - T_A))$, where T_2 is the second target which represents a lowest priority job exit feed target, F_s is a specific feed count which represents a cumulative feed count for a particular job exit, R_o is an overall request sum which represents the sum of feed requests for any or all job exits, R_s is a specific request sum, and T_A is a target adjustment which represents an adjustment of the first target and the second target.

26. The method according to claim 15 wherein the determining step comprises the step of:

entering a selection of the pattern into buttons, associated with a screen of the user interface, on a page-by-page basis with a respective choice of output destinations for each page of the output set.

ABSTRACT OF THE DISCLOSURE

A printing system comprises at least two input sources for storing a printable medium prior to printing. The printing system also includes at least two output destinations for holding or processing the printable medium after the printing. A user interface supports a user's selection of one of the output destinations for any sheet of a print job in at least one of the input sources prior to the printing. A central processing unit determines a pattern of media feeds for each output set to achieve a desired appearance characteristic for the output set or the print job associated with the output destinations. The central data processing unit creates media feed instructions based on the pattern of media feeds.




FIG. 1




FIG. 2

FIG. 3




FIG. 4




FIG. 5 A




FIG. 5 B




FIG. 5C





FIG. 5D



Page Identifier	Printing Indicator	Output Destination
4	True	second . Output Dest.
8	True	second Output Dest.
12	True	second Output Dest.
13	True	first output dest.

FIG. 7A




FIG. 7B




FIG. 7C

Table 2: Example of a Balanced MediaExit Pattern

Page Identifier	Printed On?	Output Destination
4	True	second output destination
8	False	first output destination
8	True	second output destination
12	False	first output destination
12	True	second output destination

FIG. 7D

Table 3: Example of an Unbalanced MediaExit Pattern

Page	Printed On?	Output Destination
4	True	<JobExit>
8	True	<JobExit>
12	True	<JobExit>
last	False	Output Destination1
last	False	Output Destination1

FIG. 8




FIG. 9





FIG. 10



006207 446560

FIG. 11

102 Paper: ▼ TabA

103 Exception Mode: ▼ <Duplex>

104 MediaExit Pattern: DefinePattern ▼

105

107 Page List: 4,8,12

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

999

1000

FIG. 13

352 Paper: ▼ TabA

353 Exception Mode: ▼ <Duplex>

354 MediaExit Pattern: DefinePattern ▼

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

15

20

25

30